

SMART

Polis
CERAMICHE
DATA - DATE: 10 LUG. 2013

SCHEMA TECNICA PRODOTTO - TECHNICAL DATA SHEET

DATI GENERALI - GENERAL DATA

SERIE-SERIES :	SMART
FORMATI-SIZES :	30X60 - 45X45 - 60X60
NOMI-NAMES :	MOVE LUCE - MOVE DUNA - MOVE FANGO - MOVE FUMO - MOVE MORO
COLORI-COLOURS :	BIANCO - BEIGE - TORTORA - GRIGIO SCURO - MARRONE WHITE - BEIGE - DOVE - DARK GREY - BROWN
SUPERFICIE-SURFACE :	MAT
NR. COLORI-NR. COLOURS :	5


ACCESSORI - ACCESSORIES

FONDI-TILES :	X	BATTISCOPA-BULLNOSE:	X
DECORI-DECORS:	X	GRADINO-STEP:	

USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno
Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile

CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

RESISTENZA AL GELO FROST RESISTANCE		SI	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) HARDNESS (MOHS)		5	UNI EN 101
RESISTENZA ALL'ABRASIONE RESISTANCE TO DEEP ABRASION		≤ 175 mm³	EN ISO 10545-6
SPESSORE THICKNESS		9,5 - 10 mm	EN ISO 10545-2
SCIVOLOSITA' SLIPPERINESS		R9	DIN 51130
RESISTENZA ALLE MACCHIE RESISTANCE TO STAINING		5	EN ISO 10545-14
RESISTENZA CHIMICA RESISTANCE TO CHEMICALS		UA-ULA-UHA	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE BENDING STRENGTH		> 35 N/mm²	EN ISO 10545-4
ASSORBIMENTO WATER ABSORPTION		≤ 0,5%	EN ISO 10545-3